



SUNBOX

IMP Daylighting System

NEW!



Palram's newest technology, SUNBOX insulated skylight, is an advanced IMP daylighting system with an in-plane, easy-to-install design using highly impact and weather resistant polycarbonate.

Overview

In response to the industrial and commercial demand for a better IMP daylighting solution, Palram is introducing an innovative, pre-assembled drop-in system that eliminates the need for additional materials and labor required for curbed installations.

To help maintain a weather-tight roof assembly, its in-plane profile eliminates damming while allowing free flow of moisture. The unit's advanced daylighting properties also provide excellent insulation and natural lighting, delivering dual energy conservation.

Backed by Palram's MetalMatch technology, the system can match virtually any metal roof profile.




Main Benefits


- Factory assembled drop-in design makes installation easy.
- Minimal framing adjustments required.
- MetalMatch™ technology will match virtually any insulated metal profile.
- In-plane design eliminates ice damming, resulting in a more cost efficient, leak-resistant installation.
- Weather and UV resistant
- Excellent light transmission up to 50%
- Impact resistant - virtually unbreakable
- High insulation R-value
- High load resistance
- Lightweight
- 10-year limited warranty

Typical Applications

- Industrial buildings
- Commercial buildings
- Architectural projects
- Public buildings
- Shopping centers
- Supermarkets



Easy installation - drop-in design



In-plane profile



See back for details.



SUNBOX

IMP Daylighting System



Property	Test Method	Result
Air Infiltration	ASTM E283	<.01cfm/ft ² @ 6.24 psf
Water Resistance	ASTM E331	Pass @ 5.43 psf
Uniform Load	ASTM E330	+/- 60 psf (5ft span)
Smoke Density	ASTM D2843	<75
Self Ignition	ASTM D1929	>650F
Extent of Burn	ASTM D635	CC1
Flame Spread	ASTM E84	<25
SHGC	NFRC 201	.49 **
U-Value	ASTM C1363	.27 BTU/hr • ft ² • °F **
R-Value	Calculated	3.7 HR • ft ² • °F **

** Depends on thickness

General Dimensions

THICKNESSES: 2", 2.5", 3", 4"

LENGTH: 10'

WIDTH: Varies with IMP manufacturer

PROFILE: Varies with IMP manufacturer




Need to Match your own Custom Profile?

Palram can match virtually any metal roof profile (minimal order requirements apply).

Talk to your Palram representative or call Palram at 800-999-9459.

Structure



PALRAM AMERICAS

9735 Commerce Circle
Kutztown, PA, 19530 USA
Tel: 800.999.9459
contact.usa@palram.com
palram.com/us



Authorized Distributor

Form 599 5A# 600245-091219 KE

© 2019 Palram Industries LTD All Rights Reserved

In as much as PALRAM Industries has no control over the use to which others may put the material, it does not guarantee that the same results as those described herein will be obtained. Each user of the material should make his own tests to determine the material's suitability for his own particular use. Statements concerning possible or suggested uses of the materials described herein are not to be construed as constituting a license under any PALRAM Industries patent covering such use or as recommendations for use of such materials in the infringement of any patent. PALRAM Industries or its distributors cannot be held responsible for any losses incurred through incorrect installation of the material. In accordance with our company policy of continual product development you are advised to check with your local PALRAM Industries supplier to ensure that you have obtained the most up to date information.

